




PH7-800-120 (Preheat Start)

UV Electronic Ballast

Technical Specification

Product Model : PH7-800-120 (230) **Input Voltage :** AC220V±20% **Ordering Code :** 7H230800120D5FHL

Product Model : PH7-800-120 (MLT) **Input Voltage :** AC100-264V **Ordering Code :** 7HMLT800120D5FHL

Starting Mode: Preheat Start, Starting Time 4-6s

Input Current : 0.52A@230V ; 1.1A@110V **Power Frequency :** 50/60Hz

Input Features: Lightning protection, $PF \geq 0.98$, Efficiency (η): 90%, THD<10, CCF<1.7

Output Power: 120W **Output Power Range :** 75-120W **Number of Lamps :** 1pc

Output Current: 800mA **Output Current Range :** 750-850mA

Auxiliary Output: Green/red LED status indication (green: normal operation; red: fault); 5 VDC/5 mA output for LED indication; dry-contact relay output for remote status feedback and control.

Output Features : Constant Current, overvoltage protection; overcurrent protection; lamp leakage detection; filament open-circuit protection; cross-wiring protection; end-of-life (EOL) Protection

Standards Compliance: IP64; CE certified

Ambient Temperature: -10 ~ 40°C **Maximum Enclosure Temperature:** <70 °C **Humidity:** 5 – 85%

Housing Construction: Aluminum housing **Housing Dimensions :** 185×56×45mm

Mounting Hole Spacing : 175mm


Connection Type: European-Style Terminal Block; **Ballast-to-Lamp Distance:** < 5 mm

Outer Carton Size : 42.5×23.5×20.5cm **Net Weight per Unit:** 0.31 kg **Quantity per Carton :** 18pcs

Gross Weight per Carton : 6KG

Compatible Lamp Models : GPH436T5L/HOGPH846T5L/HOGPH893T5L/HOGPH1000T5L/HOGPH1148T5L/HO
GHO36T5LTUV55W/HOTUV60W/HOTUV75W/HOTUV36T5/HO TUV95W/HOPL-LTL100W

Applications: Wastewater treatment, water purification, exhaust-gas treatment, air purification, printing, pharmaceuticals, medical care, food processing, aquaculture, etc.



Dimensions: 185×56×45mm



International Sales & Export:
Wenzhou Chaoneng Water Treatment Equipment Co., Ltd.
Address: Yueqing Science & Technology Incubation and Entrepreneurship Center
(National-Level Technology Business Incubator), No. 261, Wei 17th Road,
Yueqing Economic Development Zone, Yueqing, Wenzhou, Zhejiang, China
Tel.: 0577-6266 6115
Mobile/WeChat/WhatsApp: +86 186 1227 8922
Email: chen@chaonenguv.com
Manufacturer:
Beijing Haoben Electronic Technology Co., Ltd.
Address: Building 3, No. 30 Shixing Street, Shijingshan Park, Zhongguancun Science Park, Beijing, China
Tel.: 010 6883 7150