



PH9-3800-400 (Preheat Start)

UV Electronic Ballast

Technical Specification

Product Model : PH9-3800-400 (230) **Input Voltage :** AC220V±20% **Ordering Code :** 9H2303800400D5FHL

Starting Mode:Preheat Start,Starting Time8-10S

Input Current : 1.74A@230V **Power Frequency :** 50/60Hz

Input Features: Lightning protection ; $PF \geq 0.98$; Efficiency (η): 90% ; THD<10 ; CCF<1.7

Output Power : 400W **Output Power Range :** 270-400W **Number of Lamps :** 1pc

Output Current : 3800mA **Output Current Range :** 3700-3900mA

Auxiliary Output: Green/red LED status indication (green: normal operation; red: fault); 5 VDC/5 mA output for LED indication; dry-contact relay output for remote status feedback and control.

Output Features : Constant Current,overvoltage protection;overcurrent protection;lamp leakage detection; filament open-circuit protection;cross-wiring protection;end-of-life(EOL) Protection

Standards Compliance: IP64; CE certified

Ambient Temperature: 10°C~40°C **Maximum Enclosure Temperature:** <70°C **Humidity:** 5% – 85%

Housing Construction: Aluminum housing **Housing Dimensions :** 250*108*56mm

Mounting Hole Spacing : 240/65mm




Connection Type: European-Style Terminal Block; Ballast-to-Lamp Distance: < 5 m

Outer Carton Size : 605*270*145mm **Quantity per Carton:** 10 pcs **Net Weight per Unit :** 0.95KG

Gross Weight per Carton : 10KG **Tare Weight (T.W.) :** 0.5kg

Compatible Lamp Models : GPHHA1515T9L, GPHHA1515T10L, GXA1500T10L, GPHHA1500T10L, NNI400/147XL, TUV330WXPT

Applications: Wastewater treatment, water purification, exhaust-gas treatment, air purification, printing, pharmaceuticals, medical care, food processing, aquaculture, etc.



Dimensions: 250*108*56mm



International Sales & Export:
Wenzhou Chaoneng Water Treatment Equipment Co., Ltd.
Address: Yueqing Science & Technology Incubation and Entrepreneurship Center
(National-Level Technology Business Incubator), No. 261, Wei 17th Road,
Yueqing Economic Development Zone, Yueqing, Wenzhou, Zhejiang, China
Tel.: 0577-6266 6115
Mobile/WeChat/WhatsApp: +86 186 1227 8922
Email: chen@chaonenguv.com
Manufacturer:
Beijing Haoben Electronic Technology Co., Ltd.
Address: Building 3, No. 30 Shixing Street, Shijingshan Park, Zhongguancun Science Park, Beijing, China
Tel.: 010 6883 7150