

PN13-425-2-20 (Instant Start)

UV Electronic Ballast

Technical Specification

Product Model : PN13-425-2-20 (230) **Input Voltage :** AC220V±10% **Ordering Code :** 13N230425220D5

Product Model : PN13-425-2-20 (110) **Input Voltage :** AC110V±10% **Ordering Code :** 13N110425220D5

Starting Mode: Instant Start, Starting Time < 1 s

Input Current : 0.19A@230 ; 0.4A@110V **Power Frequency :** 50/60Hz

Input Features: Lightning protection ; PF0.98 ; **Efficiency (η):** 90%

Output Power : 2*20W

Output Power Range : 10-21W

Number of Lamps : 2pcs

Output Current : 425mA

Output Current Range : 300-425mA

Auxiliary Output : lamp ON Output: DC 5 V / 5 mA (for External LED Indicator)

Output Features: Non-constant-current operation

Standards Compliance: IP64; CE certified

Ambient Temperature: -10°C~40°C

Maximum Enclosure Temperature: <70°C

Humidity: 5 – 85%

Housing Construction: Aluminum housing with U.S.-style potting compound

Housing Dimensions : 165*38*26mm

Mounting Hole Spacing : 160mm

Connection Method: 0.5 mm² multi-strand wire, length 330 mm; distance between ballast and lamp <1 m

Outer Carton Size : 425*235*205mm

Net Weight per Unit : 0.2KG




Quantity per Carton: 50 pcs

Gross Weight per Carton : 11KG

Tare Weight (T.W.) : 0.5kg

Compatible Lamp Models : GPH212T5, GPH287T5, GPH303T5, GPH436T5 , TUV10T5, TUV11T5, TUV15T5, TUV16T5

Applications: Wastewater treatment, water purification, exhaust-gas treatment, air purification, printing, pharmaceuticals, medical care, food processing, aquaculture, etc.



Dimensions: 165*38*26mm



International Sales & Export:
Wenzhou Chaoneng Water Treatment Equipment Co., Ltd.
Address: Yueqing Science & Technology Incubation and Entrepreneurship Center
(National-Level Technology Business Incubator), No. 261, Wei 17th Road,
Yueqing Economic Development Zone, Yueqing, Wenzhou, Zhejiang, China
Tel.: 0577-6266 6115
Mobile/WeChat/WhatsApp: +86 186 1227 8922
Email: chen@chaonenguv.com
Manufacturer:
Beijing Haoben Electronic Technology Co., Ltd.
Address: Building 3, No. 30 Shixing Street, Shijingshan Park, Zhongguancun Science Park, Beijing, China
Tel.: 010 6883 7150