RC: 7124366

CHEZLUBE
Petroleum Limited

P R O D U C T

Berger XHD 15W/40 API *CI-4/SL*

Market Applications

These heavy duty engine oil is recommended for all types of diesel and gasoline engines where the manufacturer specifies the API service CI-4/SL. Berger XHD 15W40 CI-4 is especially suited for use in low temperature environments where extreme pumpability properties are required. These Oil is also suitable for on-road and off-road applications, including equipment that are exposed to extreme low temperature operations. This oil is suitable for use in moderate to high sulfur content fuel.

Product Description

Berger XHD CI-4 of multifunctional engine lubricants are blended from high quality minerals oils and feature on advanced additive package. It greatly exceeds the generally accepted performance levels of lubricant produced to meet the requirements of the above specifications.

Benefits

Berger XHD CI-4 saves on fleet maintenance cost. The detergency/dispersancy level is specially balanced to provide both high temperature deposit control in a wide range of heavy duty and turbocharged diesel engines. Reduce Downtime and prolong engine life. Universal engine oil for cars, trucks and off-road applications.

This product meets or exceeds the requirements of: API CI-4

API CH-4
API CG-4
API CF-4
API CF
API SL
API SJ

TYPICAL DATA:

CHEZLUBE XHD CI-4	
Density @ 20 deg c(kg/l)	0,85
Viscosity @ 40 deg c (mm2/s)	110.00
Viscosity @ 100 deg c (mm2/s)	14,20
VI	130
Flash point COC (deg C)	230
Pour point (deg C)	-33

Total Base Number, mgKOH/g, ASTM D2896
11

Ash, Sulfated, mass%, ASTM D874Pas load stage
12.60

Pack Size: 210 litres, Bulk