CHEZ LUBE
Petroleum Limited
RC: 712466

MarineX EP 2

EP 2 Grease

APPLICATIONS

EP Grease for Multipurpose Applications

MarineX EP2 is a tackified Extreme Pressure multipurpose grease for general lubrication under normal and wet operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions. It is specifically applicable in maritime industry.

General Lubrication

Lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal.
Pre-eminently suitable for passenger car, light truck and leisure vehicle applications.

Recommendation

Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

ADVANTAGES

Miscible

MarineX EP2 is miscible with most other conventional soap greases.
Excellent mechanical stability avoiding ejection or loss of consistency during operation.

Pumpability

Excellent pumpability due to the low temperature characteristics and smooth texture.
Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained.

No harmful substances

MarineX EP2 does not contain lead, or other heavy metals considered harmful to human health and the environment.

CHARACTERISTICS

	METHODS	UNITS	MarineX EP2
Soap/ Thickener		-	Lithium/CaSulfonate
NLGI Grade	ASTM D 217/DIN 51 818	-	2
Colour	Visual	-	Orange
Appearance	Visual	-	Smooth
Operating Temperature range		**°C**	**-5 to 120**
Penetration @ 25 °C	**ASTM D 217/DIN51 818**	**0.1 mm**	**275**
Anti-rust performance SKF- EMCOR	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0-0
Dropping point	**IP 396/DIN ISO 2176**	**°C**	**≥170**
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/IP71	mm²/s (cSt)	150

The typical characteristics mentioned represents mean values